



→ Column lift for trucks, trailers & semi-trailers

## DH-VO.15.K1 • 1000 - 1500 kg



# Heavy-duty column lift with manual or hydraulic closure

The DH-VO.15.K1 serves the **heavy end of the distribution market**. It is available with a **weight-saving aluminium platform**, or a **robust steel platform** in hot-dip zinc plated finish. In standard configuration, the platform is opened and closed manually. For steel platforms, DHOLLANDIA recommends **hydraulic closure to optimize the user comfort** [option OVH004]. The basic lift offers maximum all-round efficiency and can be further equipped with numerous value-adding options to adapt the lift to particular applications, such as:

- Roll-stops, hinged ramps on 2 or 3 sides
- Various types of **safety rails**, incl. rails offering side access
- K9 execution with lifting height above the vehicle floor level. See page 219
- Gas-bottle lifts. See page 220.
- Adaption for barn doors

## Lift capacity

<b>DH-VO.15.K1</b>
1000 kg
1500 kg



## Technical specifications

Lift system	<b>Lower beam:</b> operated by a single lift cylinder mounted in a steel beam at the vehicle floor level and a set of chains & pulleys
Open / Close	<ul style="list-style-type: none"> <li>• Manual closure supported by torsion bars</li> <li>• Hydraulic closure as an option [OVH004]</li> </ul>
Type of ride [see pg. 8-9]	Flat platform, level ride
Standard platform	<ul style="list-style-type: none"> <li>• Flat platform with fixed leading edge</li> <li>• Roll-stops &amp; hinged ramps available as an option</li> </ul>
Platform material	<ul style="list-style-type: none"> <li>• Reinforced steel platform, or</li> <li>• Weight-saving aluminium platform; or</li> <li>• Air-permeable aluminium platform with steel mesh [OVP509.A]</li> <li>• Air-permeable steel platform with steel grids [OVP509.G]</li> </ul>
Standard platform depths	<ul style="list-style-type: none"> <li>• 1000 - 1250 - 1500 mm</li> <li>• Other platform sizes on request</li> <li>• Max. depth = 2000 mm (condition = OVH004 + OVU019 platform support by means of side chains) or 2300 mm (condition = OVH004.2 + OVU019)</li> </ul>
Std. control unit [see pg. 10]	OAE030.BT
Standard finish of the lift frame	Galvanised steel columns with bolted-on cylinder beam